

## DOR-O-MATIC

### **ATTENTION: DYNAMIC BRAKE HARNESS NOW REQUIRED FOR MID-SWING™**

This past September, Dor-O-Matic updated its Astro, Senior, and Mid-Swing packages to make them fully compliant with new U.L. requirements. The Mid-Swing control box included with this notice is a U.L. style control box and can be easily identified by the fuse holder in the motor voltage harness.

**IF YOU INTEND TO USE THIS CONTROL BOX IN AN EXISTING INSTALLATION WITH MID-SWING MOTOR GEARBOX (83800-901/-902/-401/-402), IT IS IMPORTANT TO ADD A DYNAMIC BRAKE HARNESS (95970-600) TO EACH MOTOR.**

If you intend to use this control box with Mid-Swing Motor Gearbox 83830-901/-902/-401/-402, it is not necessary to add a dynamic brake harness.

The dynamic brake harness has two plugs that connect to the motor and the control box. The housing attaches easily to the operator. It is simple to install, and your customers will appreciate having the very latest product upgrade to ensure complete safety on their Mid-Swing installation.

Note: When servicing doors in applications that currently use the 83800-901/-902/-401/-402 motor gear box assembly without a dynamic brake, use extreme caution as the door will slam when the control box is disconnected from the motor.